

CASE SPECIFICATIONS:

REFRIGERATION:
 LOAD: 11,300 BTU/hr
 COIL TEMP: 25°F
 SUCTION STUB: 5/8IN ODS
 LIQUID STUB: 3/8IN ODS


ELECTRICAL 115V, 60HZ, 1PH
 EVAP. FANS: 1.66A
 LIGHTS: 1.2A
 COND. PUMP: 1.0A
 TOTAL: 3.86A
 MCA: 15.0A

ELECTRICAL 208/230V, 60HZ, 1PH
 EVAP. PAN: 7.2A
 1 1/2HP COND. UNIT: 12.9A
 TOTAL: 20.1A
 MCA: 24.8A



NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:			 börgeren systems	DRAWN BY: D HUNT	
SIGNATURE:		2-18-15	DRH		SCALE: 1:32	CHECKED BY:
		4-1-10	DRH		DATE: 7-21-00	
		2-26-10	DRH			
		6-16-08	DRH	4DR, 8FT HUTCH		
		DATE	REV.	DWG.	INCH	DRAWING NUMBER
		REVISION	TOL:			P3503