

CASE SPECIFICATIONS:


REFRIGERATION
LOAD: 8,500 BTU/hr
COIL TEMP: 22° F
LIQUID STUB: 3/8IN ODS
SUCTION STUB: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
EVAP. FANS: .26A
LIGHT BALLAST: .94A
CONDENSATE PUMP: 1.0A
TOTAL: 2.20A
MCA: 15.0A

ELECTRICAL 230VAC, 60HZ, 1PH.
EVAP. PAN: 7.2A
1 1/4HP COND. UNIT: 9.6A
TOTAL: 16.8A
MCA: 22.1A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:	 börger systems		DRAWN BY: D HUNT
SIGNATURE:				SCALE: 1:24
		6FT RFO TALL		
DATE	REV.	DIM:	INCH	DRAWING NUMBER
REVISION		TOL:		P4710