

CASE SPECIFICATIONS:

REFRIGERATION

LOAD: 3,900 BTU/hr
 SUCTION TEMP: 20° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.


EVAP. FANS: 1.56A
 LIGHT BALLAST: 1.0A
 COND. PUMP: 1.0A
 SOUP WELLS: 27.6A
 TOTAL: 31.16A
 MCA: 40.0A

ELECTRICAL 208/230VAC, 60HZ, 1PH.

EVAP. PAN: 7.2A
 3/4HP COND. UNIT: 6.1A
 TOTAL: 13.3A
 MCA: 16.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:	 börger systems		SCALE: 1:32	DRAWN BY: D HUNT
SIGNATURE:				8-29-06 DRH	DATE: 6-3-06
		8-4-06 DRH	4' SOUP BG-4SHL		
		7-26-06 DRH			
		7-25-06 DRH			
DATE	REV.	DIR:	INCH	DRAWING NUMBER	
REVISION	TOL:			P4880A	