



CASE SPECIFICATIONS:
 REFRIGERATION:
 CASE LOAD: 3,900 BTU/hr
 SUCTION TEMP: 22° F
 LIQUID STUB: 3/8IN ODS
 SUCTION STUB: 5/8IN ODS

AIR DISCHARGE:
 28° F @ 300 FPM

INITIAL DEFROST SETTING
 6 PER DAY @ 40 MIN. EACH

ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: .36A
 LIGHT BALLAST: 1.48A
 TOTAL: 1.84A
 MCA: 15.0A



NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:			DRAWN BY: D HUNT
SIGNATURE:				CHECKED BY:
		6-19-09 DRH	SCALE: 1:32	
		12-15-06 DRH	DATE: 10-12-06	
		11-20-06 DRH	4' SOUP BG-4SHL	
		11-10-06 DRH		
		DATE	REV.	DIM: INCH
		REVISION	TOL:	DRAWING NUMBER P4941