

CASE SPECIFICATIONS:

REFRIGERATION
 LOAD: 3,900 BTU/hr
 SUCTION TEMP: 20° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS


ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: 1.56A
 LIGHT BALLAST: 1.0A
 COND. PUMP: 1.0A
 SOUP WELLS: 27.6A
 TOTAL: 31.16A
 MCA: 40.0A

ELECTRICAL 208/230VAC, 60HZ, 1PH.
 EVAP. PAN: 7.2A
 3/4HP COND. UNIT: 6.1A
 TOTAL: 13.3A
 MCA: 16.0A



NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):		DATE:		 börger systems	
SIGNATURE:					
				DATE: 10-12-06	CHECKED BY:
		11-10-06 DRH		4' SOUP BG-4SHL	
DATE	REV.	DWG.	INCH	DRAWING NUMBER	
REVISION	TOL.			P4941A	