

CASE SPECIFICATIONS:


TOP AREA: 85.5
SQR FT

REFRIGERATION LOAD: 12,300 BTU/hr
COIL: CTA 46-123
SUCTION TEMP: 30° F
LIQUID: 3/8IN ODS
SUCTION: 7/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
EVAP. FANS: 4.4A
LIGHTS: 7.5A
TOTAL: 11.9A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:	 börger systems		SCALE: 1:32	DRAWN BY: D. HUNT	
SIGNATURE:				DATE: 10-30-06	CHECKED BY:	
		11-8-06 DRH	10 x 10, 1 BTD WINE CSRV			
		11-6-06 DRH	DATE	REV	DM	INCH
		REVISION	TOL			P4953A