



CASE SPECIFICATIONS:

REFRIGERATION
LOAD: 3,900 BTU/hr
SUCTION TEMP: 20° F
LIQUID LINE: 3/8IN ODS
SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
EVAP. FANS: 1.56A
LIGHT BALLAST: 1.0A
COND. PUMP: 1.0A
SOUP WELLS: 27.6A
TOTAL: 31.16A
MCA: 40.0A

ELECTRICAL 208/230VAC, 60HZ, 1PH.
EVAP. PAN: 7.2A
3/4HP COND. UNIT: 6.1A
TOTAL: 13.3A
MCA: 16.0A



NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):		DATE:			
SIGNATURE:					
		SCALE: 1:32	DRAWN BY: D HUNT		
		DATE: 2-5-07	CHECKED BY:		
		4' SOUP BG-4SHL			
DATE	REV	DM	INCH	DRAWING NUMBER	
REVISION	TOL			P5012A	