

CASE SPECIFICATIONS:

REFRIGERATION
 LOAD: 16,000 BTU/hr
 COIL TEMP: 25° F
 LIQUID STUB: 3/8IN ODS
 SUCTION STUB: 5/8IN ODS


ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: 1.2A
 LIGHT BALLAST: 1.88A
 TOTAL: 3.08A
 MCA: 15.0A

ELECTRICAL 230VAC, 60HZ, 1PH.
 (2) 1HP COND. UNIT: 9.2A
 TOTAL: 18.4A
 MCA: 25.2A



NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:	 börgeren systems		DRAWN BY: D HUNT
SIGNATURE:				SCALE: 1:24
		DATE: 5-21-07	12FT RFO	
		3-5-13 DRH		
DATE	REV.	DIM:	INCH	DRAWING NUMBER
REVISION	TOL:			P5121