

CASE SPECIFICATIONS:


REFRIGERATION  
 LOAD: 4,025 BTU/hr  
 SUCTION TEMP: 25° F  
 LIQUID LINE: 3/8IN ODS  
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.  
 EVAP. FANS: .30A  
 LED LIGHTS: 3.6A  
 TOTAL: 3.9A  
 MCA: 15.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



|                        |      |                  |      |   |             |
|------------------------|------|------------------|------|---|-------------|
| AUTHORIZATION (PRINT): |      | DATE:            |      |  <b>börgeren systems</b> |             |
| SIGNATURE:             |      |                  |      |   |             |
|                        |      |                  |      | DATE: 7-25-07   | CHECKED BY: |
|                        |      | 3 DOOR 42DP TALL |      |   |             |
| DATE                   | REV. | DWG:             | INCH | DRAWING NUMBER  |             |
| REVISION               | TOL: |                  |      | P5173   |             |