

CASE SPECIFICATIONS:

REFRIGERATION:

LOAD: 6,480 BTU/hr

SUCTION TEMP: 20°F

SUCTION LINE: 5/8" IN ODS





LIQUID LINE: 3/8" IN ODS

ELECTRICAL 115V, 60HZ, 1PH

EVAP. FANS: 0.13A

TOTAL: 0.13A

MCA: 15.0A



NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):		DATE:		 börger systems	
SIGNATURE:					
				SCALE: 1:32	DRAWN BY: D HUNT
				DATE: 12-18-07	CHECKED BY:
		3-17-08 DRH		6FT LPM W/DRAWERS	
DATE	REV.	DATE	REV.	DIM: INCH	DRAWING NUMBER
REVISION		TOL:			P5275A