

CASE SPECIFICATIONS:

TOP AREA: 104.8 SQR FT


REFRIGERATION LOAD: 13,300 BTU/hr
 COIL: CTA 46-140
 SUCTION TEMP: 26° F
 LIQUID: 3/8IN ODS
 SUCTION: 7/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
 (1) EVAP. COIL FANS: 4.4A
 TOTAL: 4.4A

LIGHTS TO BE DETERMINED

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:			 börger systems	
SIGNATURE:		SCALE: 1:48	DRAWN BY: D HUNT		
		DATE: 2-25-08	CHECKED BY:	1BTD CSRV WINE	
		6-23-08 DRH			
		6-16-08 DRH			
		DATE	REV.	DIM: INCH	DRAWING NUMBER
		REVISION	TOL:		P5340A