

**CASE SPECIFICATIONS:**

**REFRIGERATION**

LOAD: 3,900 BTU/hr  
 COIL TEMP: 22° F  
 LIQUID STUB: 3/8IN ODS  
 SUCTION STUB: 5/8IN ODS

**ELECTRICAL 115VAC, 60HZ, 1PH.**


EVAP. FANS: 1.56A  
 LIGHT BALLAST: 1.0A  
 COND. PUMP: 1.0A  
 SOUP WELLS: 20.7A  
 TOTAL: 24.26A  
 MCA: 40.0A

**ELECTRICAL 208/230VAC, 60HZ, 1PH.**

EVAP. PAN: 7.2A  
 3/4HP COND. UNIT: 6.1A  
 TOTAL: 13.3A  
 MCA: 16.0A

**NOTES:**

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:	 <b>börger systems</b>		DRAWN BY: D HUNT
SIGNATURE:				SCALE: 1:32
		11-25-08 DRH	4' SOUP BG-4SHL	
		11-24-08 DRH		
DATE	REV.	DWG.	INCH	DRAWING NUMBER
REVISION	TOL:			P5532