


**CASE SPECIFICATIONS:**

REFRIGERATION  
 LOAD: 6,600 BTU/hr  
 SUCTION TEMP: 25° F  
 LIQUID LINE: 3/8IN ODS  
 SUCTION LINE: 1/2IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.  
 EVAP. FANS: 1.2A  
 TOTAL: 1.2A  
 MCA: 15.0A

**NOTES:**

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):		DATE:		 <b>börgeren systems</b>		SCALE: 1:32		DRAWN BY: D HUNT	
SIGNATURE:						DATE: 10-5-10		CHECKED BY:	
				11-22-13 DRH		8FT LPM FIELD OF FLOWERS			
DATE		REV.		DIM:		INCH		DRAWING NUMBER	
								P5894	