



TOP VIEW  
SCALE 1/12

**NOTES:**

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

**CASE SPECIFICATIONS:**

**REFRIGERATION ESTIMATIONS:**

LOAD: 6,900 BTU/hr  
 COIL TEMP: 22° F  
 LIQUID STUB: 3/8IN ODS  
 SUCTION STUB: 5/8IN ODS

ELECTRICAL 208/230VAC, 60HZ, 1PH.

EVAP. FAN: 0.22A  
 3/4HP COND. UNIT: 6.8A  
 EVAP PAN: 7.2A  
 TOTAL: 15.42A  
 MCA: 18.22A

REVISION HISTORY	
DATE	APPROVED
2/4/11	SEH
2/25/11	SEH
11/16/11	SEH

		Borgen Systems 1901 Bell Avenue, Suite 2 Des Moines, IA 50315 www.borgensystems.com	
		DATE: 11/2/2010	SCALE 1/12
3FT End Cap			
DIM: INCH			DRAWING NUMBER: P5896
TOL:			