

**CASE SPECIFICATIONS:**

TOP AREA: 132.5 SQR FT

REFRIGERATION LOAD: 13,000 BTU/hr

COIL: CTA 48-130

COIL TEMP: 30° F

LIQUID STUB: 3/8IN ODS

SUCTION STUB: 7/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.

EVAP. FANS: 4.4A


TOFFER LIGHTS: 1.88A

TOTAL: 6.28A

MCA: 15.0A

**NOTES:**

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):		DATE:		 <b>börger systems</b>		SCALE: 1:48		DRAWN BY: D HUNT	
SIGNATURE:						DATE: 1-5-11		CHECKED BY:	
				2 BTD CSRV WINE		DATE		DRAWING NUMBER	
						REVISION		TOL:	