



CASE SPECIFICATIONS:

REFRIGERATION
 LOAD: 6,600 BTU/hr
 COIL TEMP: 25° F
 LIQUID STUB: 3/8IN ODS
 SUCTION STUB: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: .60A
 TOTAL: .60A
 MCA: 15.0A

ELECTRICAL 230VAC, 60HZ, 1PH.
 EVAP. PAN: 7.2A
 3/4HP COND. UNIT: 6.8A
 TOTAL: 14.0A
 MCA: 16.8A



NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

| | | | | | |
|------------------------|-------|--------------------------|------|---------------|------------------|
| AUTHORIZATION (PRINT): | DATE: | börgen systems | | SCALE: 1:32 | DRAWN BY: D HUNT |
| SIGNATURE: | | | | DATE: 4-13-11 | CHECKED BY: |
| | | 6FT LPM FIELD OF FLOWERS | | | DRAWING NUMBER: |
| DATE | REV. | BY: | INCH | P6023 | |
| REVISION | TOL. | | | | |