



CASE SPECIFICATIONS:

REFRIGERATION:  
CASE LOAD: 2,700 BTU/hr  
COIL TEMP: 22° F  
LIQUID STUB: 3/8IN ODS  
SUCTION STUB: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.  
LIGHTS & FANS: 2.4A  
TOTAL: 2.4A  
MCA: 15.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



AUTHORIZATION (PRINT):		DATE:				SCALE: 1:24		DRAWN BY: D HUNT	
SIGNATURE:						DATE: 3-13-13		CHECKED BY:	
				6-18-13 DRH		6FT DELI GRAVITY			
				3-15-13 DRH					
		DATE		REV.		DIM: INCH		DRAWING NUMBER	
		REVISION		TOL:				P6380	