



CASE SPECIFICATIONS:

REFRIGERATION:

CASE LOAD: 7,400 BTU/hr
 COIL TEMP: 22° F
 LIQUID STUB: 3/8IN ODS
 SUCTION STUB: 5/8IN ODS

AIR DISCHARGE:

28° F @ 250 FPM

INITIAL DEFROST SETTING

6 PER DAY @ 40 MIN. EACH

ELECTRICAL 115VAC, 60HZ, 1PH.

EVAP. FANS: .8A

TOTAL: .8A

MCA: 15.0A

ADDITIONAL CONNECTIONS FOR:

LIQUID LINE SOLENOID VALVE
 DISCHARGE AIR PROBE

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):		DATE:		börger systems	
SIGNATURE:					
		SCALE: 1:24	DRAWN BY: DWIT		
		DATE: 3-6-07	CHECKED BY:		
		8FT SINGLE DECK			
		8-25-14	DRH		
DATE	REV.	DIM: INCH		DRAWING NUMBER	
REVISION	TOL:			P4984	