


**CASE SPECIFICATIONS:**

**REFRIGERATION**

LOAD: 20,000 BTU/hr  
 COIL TEMP: 22° F  
 LIQUID STUBS: 3/8IN ODS  
 SUCTION STUBS: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.  
 EVAP. FANS: 3.12A  
 LIGHT



**NOTES:**

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



AUTHORIZATION (PRINT):	DATE:					SCALE: 1:48		DRAWN BY: D HUNT	
SIGNATURE:						DATE: 6-4-09		CHECKED BY:	
		7-21-09 DRH		PRODUCE PREP 4W8W4					
		DATE	REV.	DIM:	INCH			DRAWING NUMBER	
		REVISION	TOL:					P5647	