



CASE SPECIFICATIONS:

REFRIGERATION:
CASE LOAD: 9,800 BTU/hr
COIL TEMP: 22° F
LIQUID STUB: 3/8IN ODS
SUCTION STUB: 5/8IN ODS

AIR DISCHARGE:
28° F @ 300 FPM

INITIAL DEFROST SETTING
6 PER DAY @ 40 MIN. EACH

ELECTRICAL 115VAC, 60HZ, 1PH.
ECM EVAP. FANS: .60A
TOTAL: .60A
MCA: 15.0A

ADDITIONAL CONNECTIONS FOR:
LIQUID LINE SOLENOID VALVE
DISCHARGE AIR PROBE



NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):		DATE:				SCALE: 1:24		DRAWN BY: D HUNT	
SIGNATURE:						DATE: 3-10-14		CHECKED BY:	
		5-23-14 DRH		8' SELF SERV. MERCH. ANGLED					
		3-19-14 DRH		DATE		REV.		DIN: INCH	
				REVISION		TOL:		DRAWING NUMBER P6610	