



CASE SPECIFICATIONS:

REFRIGERATION:

CASE LOAD: 11,100 BTU/hr  
 COIL TEMP: 22° F  
 LIQUID STUB: 3/8IN ODS  
 SUCTION STUB: 5/8IN ODS

AIR DISCHARGE:

28° F @ 250 FPM

INITIAL DEFOST SETTING

6 PER DAY @ 40 MIN. EACH

ELECTRICAL 115VAC, 60HZ, 1PH.

EVAP. FANS: 1.2A  
 TOTAL: 1.2A  
 MCA: 15.0A

ADDITIONAL CONNECTIONS FOR:

LIQUID LINE SOLENOID VALVE  
 DISCHARGE AIR PROBE

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFOST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):		DATE:		<b>börger systems</b>	
SIGNATURE:					
		SCALE: 1:24	DRAWN BY: D HUNT		
		DATE: 4-2-14	CHECKED BY:		
12FT SINGLE DECK					
DATE	REV.	DR:	INCH	DRAWING NUMBER	
REVISION	TOL:			P6632	