

#### CASE SPECIFICATIONS:

##### REFRIGERATION:

CASE LOAD: 6,200 BTU/hr

COIL TEMP: 22° F

LIQUID STUB: 3/8IN ODS

SUCTION STUB: 5/8IN ODS

##### AIR DISCHARGE:

28° F @ 300 FPM

##### INITIAL DEFROST SETTING

6 PER DAY @ 40 MIN. EACH

ELECTRICAL 115VAC, 60HZ, 1PH.

EVAP. FANS: .60A

LED LIGHTS: 1.2A

TOTAL: 1.8A

MCA: 15.0A

##### ADDITIONAL CONNECTIONS FOR:

LIQUID LINE SOLENOID VALVE

DISCHARGE AIR PROBE


REAR FAN CONTROL RELAY

PANS: (10) 1/4 SIZE W/LIDS INCLUDED  
STANDARD



#### NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):		DATE:		 <b>börger systems</b>		DRAWN BY: D HUNT	
SIGNATURE:						BG6PLHB	
				SCALE: 1:24			
				DATE: 2-23-16			
				6 FOOD PREP LOW HYBRID			
DATE	REV.	DWG.	INCH			DRAWING NUMBER	
REVISION	TOL:					P7040	