



CASE SPECIFICATIONS:

REFRIGERATION

LOAD: 6,900 BTU/hr
 COIL TEMP: 25° F
 LIQUID STUB: 3/8IN ODS
 SUCTION STUB: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: .60A
 LIGHTS: 3.6A
 CONDENSATE PUMP: 1.0A
 EVAP. PAN: 3.0A
 TOTAL: 8.2A
 MCA: 15.0A

ELECTRICAL 230VAC, 60HZ, 1PH.
 1HP COND. UNIT: 7.7A
 TOTAL: 7.7A
 MCA: 10.8A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 INCH NATIONAL PIPE STRAIGHT THREAD.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



börger systems

9-4-12	DRH				
6-11-09	DRH				DRAWN BY: D. HUNT
0-23-02	DRH	SCALE: 1:16			CHECKED BY:
0-16-98	DRH	DATE: 8-10-96			
8-4-98	DRH				
1-27-96	DRH				
DATE	REV	DN:	INCH		DRAWING NUMBER
REVISION		TOL:			P2248

5 DOOR