

CASE SPECIFICATIONS:


REFRIGERATION

LOAD: 9,000 BTU/hr
 SUCTION TEMP: 20° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: .26A
 LIGHT BALLAST: 1.48A
 TOTAL: 1.74A
 MCA: 15.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

| | | | | |
|------------------------|-------|-------------------------------------------------------------------------------------------------------------|----------------------|------------------|
| AUTHORIZATION (PRINT): | DATE: |  börger systems | | DRAWN BY: D HUNT |
| SIGNATURE: | | | | SCALE: 1:24 |
| | | DATE: 12-13-96 | 1DR OPEN 45 CMB LEFT | |
| | | 10-3-06 DRH | | |
| DATE | REV. | DIM: | INCH | DRAWING NUMBER |
| REVISION | TOL: | | | P2411A |