

CASE SPECIFICATIONS:


REFRIGERATION:
 LOAD: 13,140 BTU/hr
 COIL TEMP: 25°F
 SUCTION STUB: 5/8IN ODS
 LIQUID STUB: 3/8IN ODS

ELECTRICAL 115V, 60HZ, 1PH
 EVAP. FANS: 2.16A
 LIGHTS: 2.4A
 COND. PUMP: 1.0A
 TOTAL: 5.56A
 MCA: 15.0A

ELECTRICAL 208/230V, 60HZ, 1PH
 EVAP. PAN: 7.2A
 1 1/2HP COND. UNIT: 12.9A
 TOTAL: 20.1A
 MCA: 24.8A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:					 börger systems	DRAWN BY: D HUNT
SIGNATURE:		2-18-15	DRH	DATE: 7-21-02			CHECKED BY:
		5-10-12	DRH	5DR, 10FT HUTCH			
		6-28-05	DRH				
		DATE	REV.	DIM:	INCH		DRAWING NUMBER
		REVISION	TOL:				P3502