



CASE SPECIFICATIONS:

REFRIGERATION:  
 LOAD: 9,640 BTU/hr  
 COIL TEMP: 25°F  
 SUCTION STUB: 5/8IN ODS  
 LIQUID STUB: 3/8IN ODS

ELECTRICAL 115V, 60HZ, 1PH  
 EVAP. FANS: 1.66A  
 LIGHTS: 1.2A  
 COND. PUMP: 1.0A  
 TOTAL: 3.86A  
 MCA: 15.0A

ELECTRICAL 208/230V, 60HZ, 1PH  
 EVAP. PAN: 7.2A  
 1 1/4HP COND. UNIT: 9.2A  
 TOTAL: 16.4A  
 MCA: 19.4A



NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:				DRAWN BY: D HUNT	
SIGNATURE:		2-18-15	DRH		SCALE: 1:32	
		12-19-11	DRH		DATE: 6-11-01	CHECKED BY:
		6-21-07	DRH			
		11-15-04	DRH		3DR, 6FT HUTCH	
		DATE	REV.	DWG.	INCH	DRAWING NUMBER
		REVISION		TOL:		P3785