

CASE SPECIFICATIONS:

REFRIGERATION


DOOR LOAD: 1,725 BTU/hr
 OPEN LOAD: 4,740 BTU/hr
 TOTAL LOAD: 6,465 BTU/hr
 SUCTION TEMP: 20° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: .26A
 LIGHT BALLAST: 1.88A
 CONDENSATE PUMP: 1.0A
 TOTAL: 3.14A

ELECTRICAL 230VAC, 60HZ, 1PH.
 EVAP. PAN: 6.5A
 1HP COND. UNIT: 9.9A
 TOTAL: 16.4A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 INCH NATIONAL PIPE STRAIGHT THREAD.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

				börger systems	
		SCALE: 1:16		DRAWN BY: D HUNT	
		DATE: 11-14-03		CHECKED BY:	
		1 DR 3 1/4FT DF LEFT CMB			
DATE	REV.	DIM: INCH		DRAWING NUMBER	
REVISION		TOL:		P4296B	