

CASE SPECIFICATIONS:

REFRIGERATION

LOAD: 8,750 BTU/hr
 COIL TEMP: 25°
 LIQUID STUB: 3/8IN ODS
 SUCTION STUB: 5/8IN ODS


ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: .90A
 LIGHT BALLAST: 2.4A
 CONDENSATE PUMP: 1.0A
 TOTAL: 4.3A

ELECTRICAL 230VAC, 60HZ, 1PH.
 EVAP. PAN: 7.2A
 1 1/2HP COND. UNIT: 10.9A
 TOTAL: 23.7A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



AUTHORIZATION (PRINT):		DATE:		 börgeren systems		DRAWN BY: D HUNT	
SIGNATURE:						CHECKED BY:	
		SCALE: 1:24					
		DATE: 2-27-04					
		2-17-10 DRH		6FT OPEN			
DATE		REV.		DIM: INCH		DRAWING NUMBER	
REVISION		TOL:				P4380	