





CASE SPECIFICATIONS:

REFRIGERATION
LOAD: 10,800 BTU/hr
COIL TEMP: 25°F
LIQUID STUB: 3/8IN ODS
SUCTION STUB: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
EVAP. FANS: .52A
LED LIGHTS: 2.4A
CONDENSATE PUMP: 1.0A
TOTAL: 3.92A
MCA: 15.0A

ELECTRICAL 230VAC, 60HZ, 1PH.
EVAP. PAN: 7.2A
1 1/2HP COND. UNIT: 10.9A
TOTAL: 18.1A
MCA: 23.7A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



AUTHORIZATION (PRINT):		DATE:		 börger systems	
SIGNATURE:					
DATE:		REV:	INCH:	DRAWING NUMBER:	
REVISION:		TOL:		P4386(B)	