



CASE SPECIFICATIONS:

REFRIGERATION:
 OPEN LOAD: 7,820 BTU/hr
 DOORED LOAD: 1,150 BTU/hr
 LOAD TOTAL: 8,970 BTU/hr
 COIL TEMP: 25°F
 SUCTION STUB: 5/8IN ODS
 LIQUID STUB: 3/8IN ODS

ELECTRICAL 115V, 60HZ, 1PH
 EVAP. FANS: 0.90A
 LIGHTS: 2.4A
 TOTAL: 3.3A
 MCA: 15A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLER), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 INCH NATIONAL PIPE STRAIGHT THREAD.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



| | | | | | | | |
|-------------|-----|------------------------|-----|-----------------------|-----|------------------|-----|
| | | | | SCALE: 1:16 | | DRAWN BY: D HUNT | |
| | | | | DATE: 6-18-04 | | CHECKED BY: | |
| 4-19-07 DRH | | 1 DR 5FT DF OPEN RIGHT | | DRAWING NUMBER: P4469 | | | |
| DATE | REV | DATE | REV | DATE | REV | DATE | REV |
| REVISION | | TOL. | | | | | |