

CASE SPECIFICATIONS:


REFRIGERATION:
 DOORED LOAD: 1,725 BTU/hr
 OPEN LOAD: 8,200 BTU/hr
 TOTAL: 9,925
 SUCTION TEMP: 20°F
 SUCTION LINE: 5/8 IN ODS
 LIQUID LINE: 3/8 IN ODS

ELECTRICAL 115V, 60HZ, 1PH
 EVAP. FANS: .65A
 LIGHT BALLASTS: 1.48A
 FRESH WATER SYSTEM: 5.5A
 TOTAL: 6.76A
 MCA: 15.0A

ELECTRICAL 208/230V, 60HZ, 1PH
 1 1/2HP COND. UNIT: 10.9A
 TOTAL: 10.9A
 MCA: 16.5A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

| | | | |
|----------------------|------|--|-------------------|
| | |  börger systems | |
| | | SCALE: 1:16 | DRAWN BY: D. HUNT |
| | | DATE: 7-30-04 | CHECKED BY: NAME |
| 1DR 6FT DF FWE COMBO | | | |
| DATE | REV. | DM: INCH | DRAWING NUMBER |
| REVISION | | TOL: ±1/32 | P4493B |