



CASE SPECIFICATIONS:

REFRIGERATION:
 DOORED LOAD: 1,725 BTU/hr
 OPEN LOAD: 5,175 BTU/hr
 TOTAL: 6,900 BTU/hr
 SUCTION TEMP: 25°F
 SUCTION LINE: 3/8" IN ODS
 LIQUID LINE: 3/8" IN ODS

ELECTRICAL 115V, 60HZ, 1PH
 EVAP. FANS: 0.26A
 LIGHT BALLASTS: 1.48A
 CONDENSATE PUMP: 1.0A
 TOTAL: 2.74A
 MCA: 15.0A

ELECTRICAL 230V, 60HZ, 1PH
 CONDENSATE PAN: 6.5A
 1 HP CONDENSING UNIT: 7.7A
 TOTAL: 14.2A
 MCA: 17.3A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:							
SIGNATURE:								
						SCALE: 1:24	DRAWN BY: D HUNT	
						DATE: 12-6-04	CHECKED BY:	
1DR 2 BAY OPEN 45 CMB RIGHT								
DATE	REV.	DIM:	INCH					DRAWING NUMBER
REVISION	TOL:					P4586		