

CASE SPECIFICATIONS:


REFRIGERATION  
 LOAD: 14,700 BTU/hr  
 SUCTION TEMP: 20°  
 LIQUID LINE: 3/8IN ODS  
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ,  
 1PH.  
 EVAP. FANS: .52A  
 LIGHT BALLAST: 2.22A  
 CONDENSATE PUMP: 2.0A  
 TOTAL: 4.74A  
 MCA: 15.0A

ELECTRICAL 230VAC, 60HZ,  
 1PH.  
 EVAP. PAN: 14.4A  
 (2)1HP COND. UNIT: 15.4A  
 TOTAL: 29.8A  
 MCA: 36.0

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:	 <b>börger systems</b>		DRAWN BY: D HUNT
SIGNATURE:				SCALE: 1:x
		DATE: 5-11-05		
		10FT DF		
DATE	REV.	DIM:	INCH	DRAWING NUMBER
REVISION		TOL:		P4659A