


CASE SPECIFICATIONS:

REFRIGERATION:
 OPEN LOAD: 7,820 BTU/hr
 DOORED LOAD: 1,150 BTU/hr
 LOAD TOTAL: 8,970 BTU/hr
 SUCTION TEMP: 20°F
 SUCTION LINE: 5/8IN ODS
 LIQUID LINE: 3/8IN ODS

ELECTRICAL 115V, 60HZ, 1PH
 EVAP. FANS: 0.39A
 LIGHT BALLASTS: 4.80A
 TOTAL: 5.19A
 MCA: 15A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 INCH NATIONAL PIPE STRAIGHT THREAD.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

		 börger systems	
SCALE:	1:16	DRAWN BY: D HUNT	
DATE:	9-27-05	CHECKED BY:	
1 DR 5FT DF OPEN LEFT			
DATE	REV	CHK	INCH
REVISION	YOU		
			DRAWING NUMBER P4729B