



CASE SPECIFICATIONS:

REFRIGERATION:
CASE LOAD: 17,100 BTU/hr
COIL TEMP: 22° F
LIQUID STUB: 3/8IN ODS
SUCTION STUB: 5/8IN ODS

AIR DISCHARGE:
28° F @ 300 FPM

INITIAL DEFROST SETTING
6 PER DAY @ 40 MIN. EACH

ELECTRICAL 115VAC, 60HZ, 1PH.
EVAP. FANS: 1.8A
LIGHT BALLAST: 4.8A
TOTAL: 6.6A
MCA: 15.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

82

32 5/16

27 1/8 DRAIN

36 9/16



COMPONENT



37X1
COMMERCIAL REFRIGERATOR
LESS CONDENSING UNIT

AUTHORIZATION (PRINT):	DATE:	börger systems	
SIGNATURE:			
		SCALE: 1:24	DRAWN BY: D HUNT
		DATE: 03-09-07	CHECKED BY:
		12' SELF SERV. MERCH.	
		5-16-13 DRH	
DATE	REV	DWG	INCH
REVISION	TOL:		
			DRAWING NUMBER P5048