



CASE SPECIFICATIONS:

REFRIGERATION  
 LOAD: 8,550 BTU/hr  
 SUCTION TEMP: 20° F  
 LIQUID LINE: 3/8IN ODS  
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.  
 EVAP. FANS: 2.08A  
 LIGHT BALLAST: 2.79A  
 CONDENSATE PUMP: 1.0A  
 TOTAL: 5.87A  
 MCA: 15.0A

ELECTRICAL 230VAC, 60HZ, 1PH  
 1 1/2 HP COND UNIT 9.6A EACH  
 EVAP PAN 14.4A  
 TOTAL: 24.0A  
 MCA: 29.3

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):		DATE:		<b>börger systems</b>	
SIGNATURE:					
		SCALE: 1:24	DRAWN BY: D HUNT		
		DATE: 03/09/07	CHECKED BY:		
6' SELF SERVICE 82					
DATE	REV.	DN:	INCH	DRAWING NUMBER	
REVISION	TOL:			P5059A	