



CASE SPECIFICATIONS:

REFRIGERATION  
 LOAD: 8,550 BTU/hr  
 COIL TEMP: 22° F  
 LIQUID STUB: 3/8IN ODS  
 SUCTION STUB: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.  
 EVAP. FANS: 1.2A  
 LIGHT BALLAST: 2.82A  
 TOTAL: 4.02A  
 MCA: 15.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



AUTHORIZATION (PRINT):		DATE:		börger systems		SCALE: 1:24		DRAWN BY: D HUNT	
SIGNATURE:						DATE: 03/09/07		CHECKED BY:	
				8' SELF SERV. MERCH.					
DATE		REV.		DIM.		INCH		DRAWING NUMBER	
REVISION		TOL:						P5060	