

CASE SPECIFICATIONS:


REFRIGERATION:  
 LOAD: 5,700 BTU/hr  
 SUCTION TEMP: 20°F  
 SUCTION LINE: 5/8 IN ODS  
 LIQUID LINE: 3/8 IN ODS

ELECTRICAL 115V, 60HZ, 1PH  
 EVAP. FANS: 1.06A  
 COND. PUMP: 1.0A  
 TOTAL: 2.06A  
 MCA: 15.0A

CU ELECTRICAL 230V, 60HZ, 1PH  
 CONDENSATE PAN: 7.2A  
 1HP COND. UNIT: 7.7A  
 TOTAL: 14.9A  
 MCA: 18.0

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):		DATE:		 <b>börgeren systems</b>		DRAWN BY: D THOMAS	
SIGNATURE:						CHECKED BY:	
				SCALE: 1:24			
				DATE: 7-27-07			
				4FT SELF SERVICE 82"			
DATE		REV.		DIM: INCH		DRAWING NUMBER	
REVISION		TOL:				P5066A	