

CASE SPECIFICATIONS:


REFRIGERATION:
DOORED LOAD: 4,835 BTU/hr
OPEN LOAD: 6,100 BTU/hr
TOTAL LOAD: 10,935 BTU/hr
SUCTION TEMP: 25°F
SUCTION LINE: 5/8" ODS
LIQUID LINE: 3/8" ODS

ELECTRICAL 115V, 60HZ, 1PH
EVAP. FANS: 0.65A
LIGHT BALLASTS: 2.22A
CONDENSATE PUMP: 1.0A
TOTAL: 3.87A
MCA: 15.0A

ELECTRICAL 230V, 60HZ, 1PH
EVAP. PAN: 7.2A
1 1/2HP COND. UNIT: 7.7A
TOTAL: 18.1A
MCA: 23.7A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:	 börger systems		DRAWN BY: D HUNT
SIGNATURE:				SCALE: 1:32
		DATE: 5-4-07	3DR 4FT OPEN RIGHT TALL	
		5-18-07 DRH	DRAWING NUMBER	
DATE	REV.	DIM: INCH	P5106A	
REVISION	TOL:			