

CASE SPECIFICATIONS:


REFRIGERATION  
 LOAD: 8,750 BTU/hr  
 COIL TEMP: 22°  
 LIQUID STUB: 3/8IN ODS  
 SUCTION STUB: 5/8IN ODS

ELECTRICAL: 115VAC, 60HZ, 1PH.  
 FANS: .60A  
 LIGHTS: 2.4A  
 TOTAL: 3.0A  
 MCA: 15.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



AUTHORIZATION (PRINT):	DATE:	 <b>börgeren systems</b>		SCALE: 1:24	DRAWN BY: D HUNT
SIGNATURE:				10-2-08 DRH	DATE: 6-3-08
		9-8-08 DRH	6FT DF OPEN TALL		
		6-11-08 DRH			
		DATE	REV.	DRG:	INCH
		REVISION	TOL:		
					DRAWING NUMBER P5422