

CASE SPECIFICATIONS:


REFRIGERATION
 LOAD: 17,500 BTU/hr
 COIL TEMP: 25°F
 LIQUID STUB: 3/8IN ODS
 SUCTION STUB: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: 1.8A
 LED LIGHTS: 3.6A
 TOTAL: 5.4A
 MCA: 15.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



| | | | | | | | | | |
|------------------------|--|-------|------|---|--|----------------|--|------------------|--|
| AUTHORIZATION (PRINT): | | DATE: | |  börgeren systems | | SCALE: 1:24 | | DRAWN BY: D HUNT | |
| SIGNATURE: | | | | | | DATE: 7-31-08 | | CHECKED BY: | |
| | | | | 10-21-14 DRH | | 12FT DF TALL | | | |
| DATE | | REV. | DIM: | INCH | | DRAWING NUMBER | | P5464 | |
| REVISION | | TOL: | | | | | | | |