





CASE SPECIFICATIONS:

REFRIGERATION GLYCOL
LOAD: 2,500 BTU/hr
GLYCOL TEMP: 25°F
%G CON: 35
GPM: 1.0
PRES. DROP: .9
STUB: 7/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
EVAP. FANS: .3A
LIGHT BALLAST: .74A
TOTAL: 1.04A
MCA: 15.0A



NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



AUTHORIZATION (PRINT):		DATE:		 börger systems	
SIGNATURE:					
				SCALE: 1:16	DRAWN BY: D HUNT
				DATE: 8-11-10	CHECKED BY:
		1 DOOR TALL (2)GE			
DATE	REV.	DIM:	INCH	DRAWING NUMBER	
REVISION		TOL:		P5856	