

CASE SPECIFICATIONS:


REFRIGERATION  
 SECTION TOTAL: 11,800 BTU/hr  
 COIL TEMP: 25° F  
 LIQUID STUB: 3/8IN ODS  
 SUCTION STUB: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.  
 EVAP. FANS: .90A  
 TOTAL: .90A  
 MCA: 15.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY STANDARD BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



|                        |       |              |                  |   |                |
|------------------------|-------|--------------|------------------|---|----------------|
| AUTHORIZATION (PRINT): | DATE: |              |                  |  <b>börger systems</b> |                |
| SIGNATURE:             |       | SCALE: 1:32  | DRAWN BY: D HUNT |   |                |
|                        |       | DATE: 3-4-11 | CHECKED BY:      | 10FT HP LPM (TALL)  |                |
|                        |       | 3-11-11 DRH  |                  |   | DRAWING NUMBER |
|                        |       | DATE         | REV:             | DIM: INCH   | P5998          |
|                        |       | REVISION     | TOL:             |   |                |