

**CASE SPECIFICATIONS:**

**REFRIGERATION:**

DOORED LOAD: 4,025 BTU/hr  
 OPEN LOAD: 8,200 BTU/hr  
 TOTAL: 12,225 BTU/hr  
 COIL TEMP: 25° F  
 LIQUID STUB: 3/8IN ODS  
 SUCTION STUB: 5/8IN ODS


ELECTRICAL 115V, 60HZ, 1PH  
 EVAP. FANS: 0.65A  
 LIGHT BALLASTS: 2.82A  
 COND. PUMP: 1.0A  
 TOTAL: 4.47A  
 MCA: 15.0A

ELECTRICAL 208/230V, 60HZ, 1PH  
 COND. PAN: 6.5A  
 1 1/2HP COND. UNIT 10.9A  
 TOTAL: 17.4A  
 MCA: 23.0A

**FLOOR DRAIN IS  
 REQUIRED**

**NOTES:**

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):		DATE:		 <b>börger systems</b>		SCALE: 1:32		DRAWN BY: D HUNT	
SIGNATURE:						DATE: 5-17-13		CHECKED BY:	
				3DR 6FT DF FWE COMBO					
DATE		REV.		DIM:		INCH		DRAWING NUMBER	
REVISION		TOL:						P6452	