

CASE SPECIFICATIONS:


REFRIGERATION
 LOAD: 17,500 BTU/hr
 SUCTION TEMP: 25°
 LIQUID STUBS: 3/8IN ODS
 SUCTION STUBS: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: 1.8A
 LIGHT BALLAST: 2.96A
 TOTAL: 4.76A
 MCA: 15.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



AUTHORIZATION (PRINT):	DATE:					 börgeren systems	DRAWN BY: D HUNT
SIGNATURE:					SCALE: 1:24		CHECKED BY:
					DATE: 5-22-13	12FT OPEN	
		DATE	REV.	DWG.	INCH		DRAWING NUMBER
		REVISION		TOL:			P6457