

#### CASE SPECIFICATIONS:


REFRIGERATION  
LOAD: 2,020 BTU/hr  
COIL TEMP: 25° F  
LIQUID STUB: 3/8IN ODS  
SUCTION STUB: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.  
EVAP. FANS: .30A  
LED LIGHTS: 1.2A  
COND. PUMP: 1.0A  
COND. PAN: 5.2A  
1/2 HP COND UNIT: 9.2A  
TOTAL: 16.9A  
MCA: 20.3A



#### NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):		DATE:		 <b>börger systems</b>	
SIGNATURE:					
		SCALE: 1:16	DRAWN BY: D HUNT		
		DATE: 11-13-13	CHECKED BY:		
		11-21-13 DRH			
		1 DOOR 1 WINDOW			
DATE	REV.	DR:	INCH	DRAWING NUMBER	
REVISION	TOL:			P6538	