

CASE SPECIFICATIONS:

REFRIGERATION
 LEFT SECTION: 9,700 BTU/hr
 RIGHT SECTION: 9,700 BTU/hr
 TOTAL LOAD: 19,400 BTU/hr
 SUCTION TEMP: 25° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: 1.8A
 LED LIGHTS: 4.8A
 FRESH WATER SYSTEM: 5.0A
 TOTAL: 11.6A
 MCA: 25.0A


WATER SUPPLY TO CASE:
 4-5 GPM @ 45-60 PSIG

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

FLOOR DRAIN
 MUST BE PROVIDED
 FOR THIS CASE



AUTHORIZATION (PRINT):		DATE:		 börgeren systems		SCALE: 1:24		DRAWN BY: D HUNT	
SIGNATURE:						DATE: 4-25-13		CHECKED BY:	
DATE	REV.	DATE	INCH			DRAWING NUMBER			
REVISION	TOL:					P6605			