

DOORED CASE SPECIFICATIONS:

REFRIGERATION
 LOAD: 2,300 BTU/hr
 SUCTION TEMP: 25° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: .30A
 LED LIGHTS: 1.2A
 1/2HP COND. UNIT: 9.2A
 TOTAL: 10.7A
 MCA: 20.0A

OPEN CASE SPECIFICATIONS:

REFRIGERATION
 LOAD: 10,800 BTU/hr
 COIL TEMP: 25°F
 LIQUID STUB: 3/8IN ODS
 SUCTION STUB: 5/8IN ODS


ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: .90A
 LED LIGHTS: 2.4A
 CONDENSATE PUMP: 1.0A
 TOTAL: 3.92A
 MCA: 15.0A

ELECTRICAL 230VAC, 60HZ, 1PH.
 EVAP. PAN: 7.2A
 1 1/2HP COND. UNIT: 12.9A
 TOTAL: 20.1A
 MCA: 24.8A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



AUTHORIZATION (PRINT):		DATE:		 börgeren systems		
SIGNATURE:						SCALE: 1:32
				DATE: 7-18-14	CHECKED BY:	
		1DR 8FT OPEN LEFT COMBO				DRAWING NUMBER
DATE	REV.	DR:	INCH			P6690
REVISION	TOL:					