

BOTTLES PER DOOR: 67
TOTAL FOR CASE: 201

CASE SPECIFICATIONS:


REFRIGERATION:

1DR LOAD: 1,516 BTU/hr
2DR LOAD: 3,034 BTU/hr
TOTAL LOAD: 4,550 BTU/hr
SUCTION TEMP: 30°F
SUCTION LINE: 5/8IN ODS
LIQUID LINE: 3/8IN ODS

ELECTRICAL 115V, 60HZ, 1PH
EVAP. FANS: 0.3A
LED LIGHTS: 4.8A
TOTAL: 5.1A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):		DATE:		 börger systems	
SIGNATURE:					
		SCALE: 1:24		DRAWN BY: D HUNT	
		DATE: 9-5-14		CHECKED BY:	
		3DR WINE TALL (2 ZONE)			
DATE	REV.	DRG	INCH		
REVISION	TOL:			DRAWING NUMBER P6706	