



**CASE SPECIFICATIONS:**

REFRIGERATION  
 LOAD: 5,200 BTU/hr  
 SUCTION TEMP: 30° F  
 LIQUID LINE: 3/8IN ODS  
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.  
 EVAP. FANS: .30A  
 LIGHT BALLAST: 2.4A  
 CONDENSATE PUMP: 1.0A  
 TOTAL: 3.7A  
 MCA: 15.0A

ELECTRICAL 230VAC, 60HZ, 1PH.  
 EVAP. PAN: 7.2A  
 1HP COND. UNIT: 7.7A  
 TOTAL: 14.9A  
 MCA: 17.7A

**NOTES:**

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:					
SIGNATURE:						
						DRAWN BY: D HUNT
						CHECKED BY:
4FT OPEN BAYS WINE						
DATE	REV.	Dwg.	INCH			DRAWING NUMBER P6855
REVISION	TOL:					